CHECK expert

Dryback floor



check-floors.com

CHECK expert

Vinyl floors can now be glued with CHECK expert. A fully bonded CHECK expert dryback floor is more hard-wearing and resilient than a floating floor covering. This makes it particularly suitable for heavy, frequent use or stressed areas. The floors are dimensionally stable and do not move. A firm bond is partly required in the cont-act areas making CHECK the perfect choice.

The bonding also supports a great reduction in impact noise. The covering and underbody form a solid unit, which leads to a reduction in running noise. CHECK expert is also the optimum solution for warm water underfloor heating systems*, as the heat is particularly well conducted from the subfloor to the surface due to the full-surface connection. All CHECK expert floors are pht-halate-free.

CHECK expert – the long-lasting option from the specialist for lasting enjoyment of the floor.



Construction

The CHECK expert vinyl floor consists of several layers, which are joined to form a plank during production. However, the click connection is not used here.



- 1 UV-coating
- 2 wear layer
- 3 decorative film
- 4 middle layer of virgin vinyl
- 5 return of virgin vinyl

Advantages CHECK expert

- suitable for damp rooms and residential conservatories*
- extraordinarily durable, robust and extremely long life
- very low construction height
- easy to clean
- warm underfoot, quiet and antistatic
- phthalat-free

Technical specifications

Connection

Bonding



Using this technique, the floor is glued over the entire surface using an adhesive. The individual planks are glued to the walls without tensi-

on and without joints. The manufacturer's instructions must be taken into account with regard to adhesive processing.

Format & special features

Format

Our floors are available in different formats and can be divided into four variants: planks, wide planks, tiles and XL tiles.







4-sided chamfer



A bevel is the slight bevelling of an edge. With a 4-sided chamfer, each individual plank is visually accentuated.

No grooves

Boards without grooves do not reveal any gaps, resulting in a smooth and harmonious appearance.



Decor overview CHECK exepert Decor overview CHECK expert

CHECK expert 0.3

Dimension: 1227 x 187 mm | Thickness: 2.0 mm | Wear layer: 0.3 mm

Planks/Box: 18 | m²/Box: 4.130 m² | Boxes/Pallet: 52 Boxes






2404E Heinrich Oak EAN: 4250055107704



2405E Theodor Oak EAN: 4250055107711



2406E Blankenburg Oak EAN: 4250055107728



2407E

Franziska Oak EAN: 4250055107735



2408E Helene Oak EAN: 4250055107742



2409E Klosterbusch Oak EAN: 4250055107759



24 10E Waltrop Oak



2411E lckern Oak EAN: 4250055107773



Julius Oak EAN: 4250055107780



2413E Scholven Oak EAN: 4250055107797

Utilisation class for private commercial use:





CHECK expert 0.55 Wide Plank







Dimension: 1219 x 229 mm | **Thickness:** 2.5 mm | **Wear layer:** 0.55 mm Planks/Box: 16 | m²/Box: 4.459 m² | Boxes/Pallet: 39 Boxes



2044E Victoria Oak EAN: 4250055107803




2045E Hellweg Oak EAN: 4250055107810



2046E Hibernia Oak EAN: 4250055107827



2047E Vondern Oak EAN: 4250055107834



2048E Anna Oak EAN: 4250055107841



2049E Bonifacius Oak EAN: 4250055107858



2068E Wilhelmine Pine EAN: 4250055107865



2069E Bismarck Pine EAN: 4250055107872



2400E Auguste Oak EAN: 4250055107889

Utilisation class for private commercial / industrial use:







CHECK expert 0.55 Tile





Dimension: 610 x 305 mm | **Thickness:** 2.5 mm | **Wear layer:** 0.55 mm Planks/Box: 20 | m²/Box: 3.716 m² | Boxes/Pallet: 44 Boxes



2110E **Nordstern Travertine** EAN: 4250055107896



2111E Rheinbaben Concrete EAN: 4250055107902



Zweckel Concrete EAN: 4250055107919



Neumühl Concrete EAN: 4250055107926









Our team is here for you.

Send us your requirements and we will solve them.

Our logistics and sales network can handle almost any task.

CHECK

Vinyl Range | Version 1/2019

CHECK is a brand of:

Koczwara Vertriebs-GmbH Suitbertstraße 22 46242 Bottrop GERMANY

check-floors.com